

DOMESTIC HOT WATER TANK

- OSHW-200F
- OSHW-300F
- OSHW-500F
- OSHW-300FD



Double Coil

Single Coil

HEATING

Domestic Hot Water Tank – Double Coil

DOMESTIC HOT WATER TANK			OSHW-200F	OSHW-300F	OSHW-500F	OSHW-300FD
General Characteristics	Water Volume	L	200	300	500	300
	Diameter	mm	640	640	810	640
	Height	mm	1,350	1,850	1,900	1,350
	Empty Weight	kg	61	100	146	106
	Tank Materials		F18 S.STEEL	F18 S.STEEL	F18 S.STEEL	F18 S.STEEL
	Color		Grey	Grey	Grey	Grey
Characteristics of Electrical Back-up	Additional Electric Heater	W	2,400	2,400	2,400	2,400
	Power supply electric heater	Ø / V / Hz	230W / 50 / 60Hz	230W / 50 / 60Hz	230W / 50 / 60Hz	230W / 50 / 60Hz
	Adjustable Thermostat	°C	0-90	0-90	0-90	0-90
Characteristics of Exchanger	Exchanger Type		Internal Single Coil	Internal Single Coil	Internal Single Coil	Double Coil
	Material Exchanger		F18 S.STEEL	F18 S.STEEL	F18 S.STEEL	F18 S.STEEL
	Maximum Water Temperature	°C	90	90	90	90
	Coil Surface	mm	2.3	3.1	4.8	3.1 / 0.97
Hydraulic Connections – Heat Pump	Inlet	mm	1"	1"	1 1/4"	1" (Sup 3/4")
	Outlet	mm	1"	1"	1 1/4"	1" (Sup 3/4")
Hydraulic connections – Domestic Hot Water Tank	Domestic hot water inlet	mm	3/4"	3/4"	1"	3/4"
	Domestic hot water outlet	mm	3/4"	1"	1"	1"
Energy Efficiency Class			B	B	B	B
Standing Heat loss	W		61	70	83	70
Number of Coil			Single	Single	Single	Double
MANDATORY OPTIONAL ACCESSORIES						
Domestic Hot Water Tank Installation Kit			PHLTA	PHLTA	PHLTA	PHLTA
OPTIONAL ACCESSORIES						
Mixing Valve			OSHA-MV	OSHA-MV	OSHA-MV	OSHA-MV
3-Way Valve			OSHA-3V	OSHA-3V	OSHA-3V	OSHA-3V